

Fitting Instructions for RAD0158BK Radiator Guard SUZUKI BANDIT GSF12508 & N '07-



In This Kit There Should Be 1x Radiator Guard (RAD0158BK) 1x M6x 25mm Long Button Head Bolt 2x M6x 35mm Long Button Head Bolts 3x M6 Washers 2x 100mm Lengths of self-adhesive Foam



Picture 1



Picture 2

R&G Racing Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <u>www.rg-racing.com</u> Email: <u>info@rg-racing.com</u>





Picture 3



Picture 4

TOOLS REQUIRED

• Socket set to include 4mm A/F & 10mm socket & wrench.

FITTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the bolt that secures the bottom of the radiator in place, as shown in picture 1.
- Remove the two bolts that secure the two top mounts of the radiator in place, as shown in picture 2.
- Offer the R&G Radiator Guard into place on the bike, ensuring that the brackets on the top of the radiator guard located on the rubber mounts at the top of the radiator, before fitting the two M6 x 35mm long button head bolts provided with washers on through the radiator guard and into the frame mounts, as shown in picture 3.
- On the bottom mount, locate the remaining M6 x 25mm long button head bolt through the remaining washer, then through the lower mount of the radiator guard and into the threaded radiator boss, before tightening, as shown in picture 4.
- Ensure the radiator guard is correctly mounted and tighten all bolts evenly.

ISSUE 1 07/10/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G Racing Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <u>www.rg-racing.com</u> Email: <u>info@rg-racing.com</u>



R&G RACING RETURNS POLICY (NON-FAULTY GOODS) Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to fully mode. statutory rights and does not refer to faulty goods.



INSTRUCTIONS DE MONTAGE POUR RAD0158BK Grille de protection SUZUKI BANDIT GSF1250S & N '07-



Le kit doit contenir : 1x Grille de protection (RAD0158BK) 1x Boulon M6x 25mm 2x Boulons M6x 35mm 3x Rondelles M6 2x 100mm Mousse autocollante



Photo 1



Photo 2

R&G Racing Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com





Photo 3



Photo 4

OUTILS REQUIS

• Jeu de clés 4mm.

Instructions de montage:

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever le boulon qui fixe le bas du radiateur en place (Photo 1).
- Enlever les 2 boulons qui fixent les 2 supports supérieurs du radiateur en place (Photo 2).
- Mettre la grille de protection R&G en place sur la moto, en veillant à ce que les supports du haut de la grille de protection soient placés dans les supports en caoutchouc sur le haut du radiateur, avant de passer les 2 boulons M6 x 35mm fournis avec les rondelles dessus à travers la grille de protection et dans les supports cadre (Photo 3).
- Sur le support du bas, placer le boulon restant M6 x 25mm à travers la rondelle restante, puis à travers le support inférieur de la grille de protection et dans le patron fileté du radiateur, avant de serrer (Photo 4).
- Veillez à ce que la grille de protection soit correctement montée puis serrer tous les boulons de façon égale.