


Fitting Instructions for CHG0001BK Radiator Guard DUCATI MONSTER 1200 '14-





In This Kit There Should Be
1x Cylinder Head Guard (CHG0001BK)
2x Spacers (6.50mm long)
2x M8 x 35mm Long Button Head Bolts





Picture 1 Picture 2







Picture 3 Picture 4



Picture 5

TOOLS REQUIRED

• Socket set to include 4mm A/F socket & wrench.

FITTING INSTRUCTIONS

- Remove the two M8 bolts on the underside of the front cylinder head, as shown in picture 1.
- Take the R&G Cylinder Head Guard and offer it up to the bike, taking care to locate the mount on the top right of the guard over the lower mount of the radiator, as shown in picture 2. The guards mount should sit between the flat plate of the bracket and the rubber mount.
- Take the twoM8 x 35mm long button head bolts and top hat spacers supplied in the kit and locate through the two lower mounting holes, as shown in pictures 3 & 4, before tightening the bolts into the underside of the front cylinder head.
- Ensure the cylinder head guard is correctly fitted and all bolts are tightened evenly.



ISSUE 1 11/04/2014 (AR)

Digital copies of these instructions are available to download from www.rg-racing.com

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms in has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.


R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



INSTRUCTIONS DE MONTAGE CHG0001BK GRILLE DE PROTECTION RADIATEUR DUCATI MONSTER 1200 '14-





Le kit doit contenir :

1x Protection Tête de Cylindre (CHG0001BK)

2x Entretoises (6.50mm de long)

2x M8 x 35mm Boulons





Photo 1 Photo 2







Photo 3 Photo 4



Photo 5

OUTILS REQUIS:

• Clé à douille 4mm.

INSTRUCTIONS DE MONTAGE:

- Enlever les 2 boulons M8 au bas de la tête de cylindre avant (photo 1).
- Prendre la protection tête de cylindre R&G et montez là sur la moto, en faisant attention à placer le support sur le coté droit supérieur de la protection sur le support inférieur du radiateur (photo 2). Les supports protection doivent se placer entre la plaque du support et le support caoutchouc.
- Prendre les 2 boulons M8 x 35mm et les entretoises chapeau supérieures fournies dans le kit puis placez les à travers les 2 trous de fixation inférieurs (photos 3 & 4) avant de serrer les boulons dans le dessous de la tête de cylindre avant.
- Veiller à ce que la protection tête de cylindre soit correctement installée et que tous les boulons soient serrés correctement.

Ces instructions de montage sont disponibles sur www.rg-racing.com

R&G Racing