



## FITTING INSTRUCTIONS FOR R&G LICENCE PLATE HANGER

Yamaha Fazer 600 '04> / FZ6 '04> (part code LP0038BK)



- NOTE YOU WILL NEED TO GLUE THE LIGHT SHROUD TO THE LED LICENCE PLATE LIGHT BEFORE FITTING USING SUPER GLUE.
- Remove seat.
- Remove the two side panels
- Undo the two bolts at the rear of the OEM licence plate holder with a 10mm ring spanner then undo the two allen bolts at the front of the unit.
- Lower OEM licence plate holder and undo wire connections. To make access to the wires easier pull the black plastic shroud up slightly and undo the bolt at the front of the cable tray, let this drop down then unclip the black plastic cover over the wires.
- Fit the R&G number plate light to the hole in the OEM plastic at the rear of the exhaust. The two studs just go through then fit the washer and nuts to hold it in place. This is very fiddly as the studs are only just long enough to get the nuts started, but once they are on they will tighten up and pull the light unit back slightly. You can pull the plastic up to make access easier
- Fit indicators of your choice to the R&G unit. If using OEM use the two plastic spacers to make them a tight fit.
- Pass the wires back through the bike.
- Refit cover back over wires and refit cable tray
- Offer R&G Tail Tidy up to bike and fit using the four button head bolts supplied.
- Reconnect the wires to the bike.
- Refit the two side panels
- Refit the seat

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

**R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



## Notice de montage

LP0038BK SUPPORT DE PLAQUE YAMAHA FZ6 600 2004->



### Conseil de montage:

- Enlevez la selle arrière
- Enlevez les deux carénages latéraux
- Désérrez les deux vis qui retiennent le support de plaque d'origine, ceci à l'aide d'une clé de 10mm, puis enlevez les deux vis allen à l'avant du support d'origine.
- Enlevez le support de plaque d'origine et déconnecter le faisceau électrique.
- Pour accéder plus facilement au faisceau, relevez légèrement la bague noire et enlever le boulon à l'avant du chemin de câbles.
- Mettez ensuite la lumière de plaque R&G sur le support d'origine à l'arrière des pots.
- Placez les rondelles et les écrous sur les deux goujons.
- Mettez ensuite les clignotants de votre choix sur le support de plaque R&G.
- Si vous utilisez les clignotants d'origine, vous devrez utiliser les deux joints en plastique pour le montage des clignotants.
- Si vous desirez mettre des clignotants adaptables, vous devrez mettre deux pièces alu pour chaque côté (pièce aluminium en forme de poire, attention au sens de montage de ces pièces dans les trous)
- Passez les câbles à travers la moto
- Refixez le cache, et le chemin de câble.
- Mettez le support de plaque R&G sur la moto, fixez à l'aide des 4 vis fournies dans le kit.
- Reconnectez les câbles.
- Remettez les carénages.
- Repositionnez la selle.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX  
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)