

Fitting Instructions for RAD0163BK Radiator Guard HONDA XL700V TRANSALP '08-





In This Kit There Should Be 2x Radiator Guard (RAD0163BK Left & Right) 2x 100mm Lengths of self-adhesive Foam





Picture 1 Picture 2







Picture 3

Picture 4

TOOLS REQUIRED

• Socket set to include 10mm socket & wrench.

FITTING INSTRUCTIONS

Right Side (as you sit on the bike)

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick
 them to the back of the radiator guard frame, so that they sit between the radiator guard and the
 radiator.
- Take the right sided radiator guard (this can be identified by having the mounting hole on the right side of the radiator guard when looking at the front (logo facing towards you)).
- Remove the bolt mounting the radiator in place, as arrowed in picture 1.
- Locate the R&G Radiator Guard into place, accessing the radiator from the front, locating the hooks around the edge and sliding downward into location, as shown in pictures 2 & 3.
- Re-fit the original bolt, ensuring it goes through the radiator guard mounting hole before locating into the threaded boss, as shown in picture 4.
- Ensure the radiator guard is correctly positioned before fully tightening the bolt.

To fit the radiator guard on the left side of the bike, follow the same procedure.

ISSUE 1 12/11/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.




INSTRUCTIONS DE MONTAGE POUR RAD0162K Grille de protection HONDA XL700V TRANSALP '08-





Le kit doit contenir : 2x Grille de protection (RAD0163BK gauche & droite) 2x 100mm Mousses autocollantes





1







Photo 3

Photo 4

Outils requis

Jeu de clés 10mm

Instructions de montage Coté droit

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Prendre la grille de protection coté droit (elle peut être identifiée par sont trou de fixation coté droit lorsque vous regarder le devant (le logo face à vous)).
- Enlever le boulon qui fixe le radiateur en place (Photo 1).
- Placer la grille R&G en place, en accédant au radiateur par l'avant, en plaçant les crochets autour du bord et en la glissant vers le bas pour la mettre en position (Photos 2 & 3).
- Remettre le boulon d'origine, en veillant à ce qu'il aille dans le trou de fixation de la grille de protection, avant de le loger dans le trou fileté (Photo 4).
- Veiller à ce que la grille de protection soit correctement positionnée avant de serrer le boulon complètement.

Suivre la même procédure pour installer la grille du coté gauche de la moto.

ISSUE 1 12/11/2013 (AR)

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com